

A Quality O-Ring Chain At An Affordable Price

The SRO series chain offer a value-priced O-ring chain that will not compromise on quality or durability. Features include lightening holes*, high-tech heat-treated steel alloys and all the exact same quality and craftsmanship that EK puts into their entire product line.

Chain	Pen		Roller Plate Thickness			Tensile	
	Dia	Length	Dia	Inner	Outer	Strengt	th
	(mm)	(mm)	(mm)	(mm)	(mm)	(lbs.)	(kN)
420SRO	3.96	17.30	7.77	1.5	1.5	4,300	19.1
428SROZ	4.50	20.80	8.51	1.8	1.8	5,300	23.5
520SRO6	5.38	19.95	10.16	2.0	2.0	8,500	37.8
525SROZ2	5.38	22.35	10.20	2.2	2.2	9,000	40.0
530SROZ2	5.38	24.00	10.20	2.2	2.2	9,000	40.0
630SRO	5.95	25.15	11.91	2.4	2.4	10,120	45.0

	Wear Life	Weight 100 Links					Optional Connecting	
Chain	Index					Link	Link	
	Std. As 100	(lbs.)	(kg)	Street	Dirt			
420SRO	1,000	1.71	0.78	100	100	SKJ	-	
428SROZ	1,000	2.27	1.03	250	200	SKJ	-	
520SRO6	1,000	3.46	1.57	650	650	MLJ	SKJ	
525SROZ2	1,000	4.10	1.86	750	650	MLJ	-	
530SROZ2	1,000	4.32	1.96	900	750	MLJ	-	
630SRO	1,000	5.90	2.68	1,000	NA	MLJ	-	

* 420SRO and 428SROZ do not utilize lightening holes

Gold available: 520SRO5, 525SROZ and 530SROZ



The Ultimate Sport Bike Chain

The SRX2 series chains are an excellent value for any street machine. The SRX2 chains feature lightening holes, reduced friction and Quadra X-Ring design which increases chain life from 1.5 to 2 times longer than a standard O-Ring chain

Chain	Pen		Roller Plate Thickness Tensile				
	Dia	Length	Dia	Inner	Outer	Stren	gth
	(mm)	(mm)	(mm)	(mm)	(mm)	(lbs.)	(kN)
520SRX2	5.38	19.95	10.16	2.0	2.0	8,500	37.8
525SRX2	5.38	22.35	10.20	2.2	2.2	9,000	40.0
530SRX2	5.38	24.00	10.20	2.2	2.2	9,000	40.0

	Wear Life	Weight	Disp.	Standard Connecting Link	Optional Connecting Link	
Chain	Index	100 Links	Max CC's			
	Std. As 100	(lbs.) (kg)	StreetDirt			
520SRX2	1,500	3.46 1.57	750 650	MLJ/SLJ	SKJ	
525SRX2	1,500	4.10 1.86	1,000 750	MLJ/SLJ	-	
530SRX2	1,500	4.32 1.96	1,000 750	MLJ/SLJ	-	

^{*} Avaliable for standard, gold.

Pitch 520/525/530/532 = 15.875 mm Width 520=6.35 mm, 525=7.94 mm, 530/532 = 9.53 mm



The Pinnacle of Chain Technology

- Ultra Strong: ZVX3 series chain easily surpasses every other brand with a tensile strength of 11,100 lbs.
- New ZX-ring: Adopted new ZX-ring and lasts 15% longer than ZVX series
- Minimising the clearance between the plates: Improved stiffness and weight (4.85/100 lbs)

Chain	Pen		Roller Plate Thickness Tensile					
	Dia	Length	Dia	Inner	Outer	Strengt	th	
	(mm)	(mm)	(mm)	(mm)	(mm)	(lbs.)	(kN)	
520ZVX3	5.38	20.80	10.20	2.2	2.4	9,400	41.8	
525 ZV X3	5.38	23.10	10.20	2.4	2.6	10,300	45.8	
530ZVX3	5.38	24.70	10.20	2.4	2.6	11,100	48.9	

	Wear Life	Weight	Disp.		Standard Connecting Link	Optional Connecting Link
Chain	Index	100 Link	s Max C	C's		
	Std. As 100	(lbs.) (kç)) Street [Dirt		
520ZVX3	2,000	3.97 1.8	01,200	NA	MLJ	SLJ
525 Z VX3	2,000	4.52 2.0	51,300	NA	MLJ	SLJ
530ZVX3	2,000	4.85 2.2	01,400	NA	MLJ	SLJ

^{*} Avaliable for standard, gold, chrome, colors (Red / Blue / Green / Yellow / Purple / Orange / Pink / White) and Metallic colors (Red / Blue / Green / Orange / Purple).